

RADIATION MONITORS

Model WLx Portable Working Level Radiation Monitor

The WLx is a sophisticated measurement system that features a state of the art solid state detector and employs sophisticated algorithms to determine the potential alpha energy concentration (primarily from radon and thoron progeny) in a given volume of air. The WLx is a laboratory grade, portable instrument. The error analysis capability is unique in a field instrument of this type. The servo controlled pump makes it well suited to unattended area level monitoring for extended periods in adverse environments.

Applications:

- Simultaneous Radon and Thoron Progeny Measurement
- Radiological Protection of Personnel
- Area Monitor (Alarm Output)
- Health Physics Studies
- Building Monitoring
- Equilibrium Ratio Measurements

Features:

- Solid state detector 25mm dia.
- Graphic display and printer
- Servo controlled pump
- RS232 port/PC software
- Barometric pressure and temperature sensors
- Volumetric air sampling
- Internal audible alarm, remote alarm contact provided
- Tamper resistant housing, portable
- Pre-programmed and User programmable measurement methods
- Simultaneous radon and thoron daughter sampling/measurement
- Reports radon and thoron WL with error approximation
- Live measurement as opposed to tail count technique
- Capability for equilibrium measurement when combined with a radon gas monitor
- Detects, measures and discriminates



WLx

radon and thoron progeny using spectroscopic analysis.

- User supplied batteries maintains basic operation during a power interruption
- Optional built in battery recharging circuit

Theory of Operation:

A working level system measures the potential alpha energy in a given volume of air. This is accomplished by sampling a known air volume by the servo controlled pump through a filter. The radon and thoron progeny in the air sample are collected on a filter that faces a laboratory grade ion implanted solid state detector. As the radon and thoron progeny decay, alpha particles are released. An alpha particle that strikes the detector releases a quantity of electrons across the semiconductor diode junction. The quantity of electrons released is proportional to the energy of the alpha particle. A multi-channel analyzer discriminates the radon and thoron progeny. Sophisticated algorithms determine the working level.



RADIATION MONITORS

Specifications:

GENERAL

Mode of Operation:	Multiple.
Sample & Count Periods	User Programmable.
Electronic Background:	< 0.1 cpm
DETECTOR	
Detector:	"Instrument quality" 25 mm dia. solid state.
Detection Range:	0.001 to 50 WL
Minimum Detectable Level:	0.001 WL - One hour continuous sample.
POWER	
Power Supply Requirements:	12 Vdc \pm 20%, 0.5 A - 110/220 VAC Adapter/Charger Included.
Battery Type(s):	6 "D cells" : Alkaline, Ni-CAD, or NiMH. - Temporary Operation and Memory Backup.
Battery Operating Time:	48 to 120 Hrs - Depending on mode of operation.
Battery Charge Time:	16 Hrs - Ni-CAD or NiMH Batteries Only. Charge circuit must be enabled.

FEATURES

Display	80 Character by 4 Line Backlit Graphic Liquid Crystal Display.
Memory	30 Days at 1 hour intervals - For Continuous Method Only.
Data Port:	RS-232 via 9 pin D-Sub Connector.

PUMP

Pump Flow Rate:	300 to 2000 sccm
Pump Flow Rate Tolerance:	\pm 5 sccm
Filter type	0.8 μ m, 25mm Millipore AAWP02500 or equivalent.

ALARMS

Alarm Level:	Programmable.
External Alarm Output:	Isolated contact, 2A nominal @ 24V.
Integrated Audible Alarm	Piezo-ceramic (70 – 85 dB).

ENVIRONMENTAL SENSORS

Temperature Sensor Tolerance:	\pm 1 °C
Barometric Pressure Sensor Tolerance:	\pm 1 kPa.

ENVIRONMENTAL

Operating Temperature Range:	0 to +50 (-32 to +122) °C (°F)
Storage Temperature Range:	-20 to +70 (-4 to + 158) °C (°F)
Relative Humidity Range:	0 to 90 % - Non-Condensing.

DIMENSIONS

Length:	25.4 (10) cm (in.)
Width:	45.1 (17.75) cm (in.)
Height:	22.9 (9) cm (in.)
Weight:	6 (13.2) kg (lb.) - With Batteries.

- Values are nominal.
- Specifications are based on new units which have been appropriately calibrated.
- Specify charging circuit requirement at time of order.

Ordering Information:

Model WLx:	Order part number 6204610.
Optional Thoron Calibration:	Order part number 9000125.

Specifications subject to change without notice.
Trademarks are the properties of their respective holders. All Rights Reserved.
Datasheet: 102 Rev 3