ACCESSORIES/SPARES

Model WG-1001

The WG-1001 series of water degassing systems (WG-1001, WG-1001A, WG-1001B, WG-1001C) allow the user to obtain radon samples from water and place them in

The WG-1001 Vacuum Water Degassing Systems are designed for accurate and rapid extraction of radon from water samples. The basic WG-1001 system consists of a vacuum and bubbler assembly and a hand-pump, all stored in a portable case. Variations of the WG-1001 kit allow you to include Pylon model 300A cells or offer the choice of optional water trap to reduce the possibility of cell damage if the vacuum is not shut off in time.



WG-1001A

Applications:

- Water quality analysis from wells and natural springs
- To monitor run-off and process water from mining, excavation, and ore processing
- Seismic prediction studies
- Prospecting for Uranium deposits under bodies of water such as lakes

Features:

- Easy to use
- Lightweight and portable
- Allows for multiple grab samples
- Available with or without cells and with or without water trap

Theory of Operation:

A vacuum is placed on the attached Lucas cell. This vacuum is used to agitate the water sample for radon gas extraction.

The excess moisture in the gas is removed via the drying tube assembly to protect the cell from moisture damage. Once the sample is placed in the cell, the amount of radon can be measured using a Pylon Model AB-5 monitor.



ACCESSORIES/SPARES

Specifications:

Extraction Efficiency: 95 % - Radon gas from a 190 ml sample using a 300A cell. Vacuum: 27 in Hg - At sea level. Maintained for a minimum of 12 hours.

Operating Temperature Range: 0 to +50 (+32 to +122) °C (°F) Storage Temperature Range: -20 to +75 (-4 to +167) °C (°F) Relative Humidity Range: 0 to 90 % - Non condensing

 Length:
 35 (13.8) cm (in.)

 Width:
 45 (17.7) cm (in.)

 Height:
 15 (5.9) cm (in.)

Weight: 6 (13.2) kg (lb.) - Without Cells. Weight: 9 (19.8) kg (lb.) - With Cells.

Ordering Information:

| Model | Part Number | Description |
|---|--|---|
| WG-1001 WG-1001A WG-1001B WG-1001C | 6215928 A215900 6215940 6215950 | Water degassing system without cells Water degassing system with 5 X 300A cells Water degassing system w/trap; w/o cells Water degassing system with trap; with cells |

TEL: 613-226 7920 FAX: 613-226 8195

instrument@pylonelectronics.com

Specifications subject to change without notice. Trademarks are the properties of their respective holders. All Rights Reserved. Datasheet: 106 Rev 2

[·] Values are nominal.